

# **How to activate the Private Extension(RFC3325)**

**(KX-UDS/UDT series)**

No. 46-002

September 20 , 2012

Ver.1.0

Panasonic Corporation

## **Abstract about this document**

This document describes about how to activate the Private Extension(RFC3325 : "P-Preferred-Identity", "Privacy" header) .

## **Revision history**


Date	Version	Revision	Firmware version
Sep 20, 2012	Ver. 1.0	Initial Release	All versions

- 1. In default settings, the P-preferred and Privacy Header will be disable.**
- 2. The below two parameters enable you to manage them.**  
**-SIP\_P\_PREFERRED\_ID**  
**-SIP\_PRIVACY**
- 3. You can configure it through a configuration file.**

# Explanation of SIP\_P\_PREFERRED\_ID parameter

## SIP\_P\_PREFERRED\_ID

Value Format	Boolean
Description	Specifies whether to add the "P-Preferred-Identity" header to SIP messages.
Value Range	<ul style="list-style-type: none"><li>• Y (Add the "P-Preferred-Identity" header)</li><li>• N (Do not add the "P-Preferred-Identity" header)</li></ul>
Default Value	N



# Explanation of SIP\_PRIVACY parameter

## SIP\_PRIVACY

Value Format	Boolean
Description	Specifies whether to add the "Privacy" header to SIP messages.
Value Range	<ul style="list-style-type: none"><li>• Y (Add the "Privacy" header)</li><li>• N (Do not add the "Privacy" header)</li></ul>
Default Value	N

