***	*** Release Note for ISIS Driver *****
	KV-S7065C / KV-S7075C / KV-S3065CW / KV-S3065CL
(c)	Panasonic Corporation 2010-2020
	======================================
1.	Update for improving security.
	The permissions of the folder where executable files are installed are changed to Read-only for general
	users.
	rsion 3.0 -> 3.1
 1.	To support 'EMC Captiva Cloud Toolkit'.
2.	To support the operating system.
	d "Windows® XP 64bit", "Windows Server® 2003", "Windows Server® 2008", "Windows Server® 2012"
,	
	rsion 2.1 -> 3.0
	User Interface is changed to Tabbed_Dialog.
2.	To support 'PreScan' function.
3.	To support 'Help' function.
==:	======================================
1.	To support 'Automatic Image Orientation' function.
2.	To support 'Background Removal' function.
3.	To support Border removal width and Remove shadow width settings.
4.	To support optional flatbed scanner KV-SS080 with KV-S3065CW/CL.
==: Vei	rsion 1.9 -> 2.0
1.	The '2-Page Separation' function is available.

2. The 'Multi Crop' function is available.

3. The 'Automatic Duplex' function in 'Paper Source' is available.

======================================		
1.	Windows Vista® 64bit edition is available.(Not pure 64bit mode)	
	======================================	
á	To improve 'Double Exposure' functions as follows. a. To support 'Apply Double Exposure to' function in 'Double Exposure'. That way, documents smaller than the selected size are scanned into one page. b. 'Double Exposure' is available to be used with 'Blank Page Removal'	
	======================================	
	Windows Vista® 32biit edition is available. Windows® 98, Windows® ME and Windows NT® are removed from support OS.	
	======================================	
1.	(Fix)White image data is gotten when 'Border Removal' and ' Smooth Background' is set at a time. (Fix)There is a case that 'Deskew' and ' Automatic Crop' function does not work when 'Smooth BackGround' function is set.	
== Ve	======================================	
1. 2. 3.	'Double Exposure' function support. Separation sheet support when scanning with 'Crop' or 'Deskew' setting. 'Select Max. Paper Size' option for 'Automatic Crop' function support. JPEG translation mode support.	

- 5. 'DocumentNumber/CounterTorigger' function for imprinter support.
- 6. 'Duplex Type' function (Select BOOK or CALENDER type) support.
- 7. 'Smooth Background' function support.
- 8. 'Resolution Rate' for 'Binary/Color Automatic distinction function support.
- The following function for 'Enhance Image' deleted.
 Crop/Deskew/ImageScaling/Rotation

- 10. Maximum Image length is changed from 25inch to 40inch.(KV-S7065C)
- 11. (Fix) Back side image rotated when 'Skip Blank Page' is set.

Version 1.2 -> 1.3

- 1. 'Binary/Color Automatic Distinction' function support.
- 2. 'TAG_LASTPAGEENDORSER' support.
- 3. (Fix) Correct color image data is not get with some application.

'PlanarConfiguration' value is set to '2'(false value) instead of '1'(true value).

4. (Fix) Scanner can not be used when the following condition.

Application: Kofax-SVRS

Interface: USB

Select wrong scanner name in 'Selected Device' of 'Configure Device Settings' dialog.

Version 1.1 -> 1.2

1. (Fix) Scanner can not be used when the following condition.

(KV-S3065CW/CL)

Application: Kofax-SVRS

Interface: USB

Version 1.0 -> 1.1

- 1. Deskew-option name is changed from "Smooth" to "Smoothing".
- 2. "Color Dropout" function support at Gray mode.
- 3. (Fix) Error occurred when scanned with the following way.
 - 1) Set 24bitColor, ColorMatching-sRGB.
 - 2) Scan.
 - 3) Push "Default" button in main setting dialog.
 - 4) Scan.
- 4. (Fix) "Custom Profiles" setting is not changed to "Temporary" when "Dots per inch" is set from keyboard.
- 5. (Fix) No-paper error occurred even if paper is on the feeder when following process is done.
 - 1) Set "Manual Feed Mode" to "Wait Key".
 - 2) Scan.
 - 3) Push scanner-stop-button to stop scanning.
 - 4) Set "Manual Feed Mode" to "Off".
 - 5) Scan.

- 6. (Fix) "Continue Scanning" process can not be done correctly when following process is done.
 - 1) Set paper in ADF. (Order: NomalPaper/NomalPaper/SimplexControlSheet/NomalPaper)
 - 2) Set "Paper Source" to Duplex, "Detect ControlSheet" to ON, "SkipControlSheet" to Off.
 - 3) Scan.
 - 4) Set 5 papers in ADF.
 - 5) Push "Continue Scanning" button. Scanning stop after 4-sheet paper is scaned.
- 7. (Fix) "Remove Shadow" function is not work in back side when "Paper Source" is changed from simplex to duplex by control sheet.
- 8. (Fix) Error occurred when scanned with Deskew-Smoothing, White-NoiseReduction setting.
- 9. (Fix) Imprinter-String is not cleard when No-Imprinter-setting is restored by using Custom-Profiles function.
- 10. (Fix) Chroma setting is enabled when scanning with "ColorMatching-sRGB" setting.

Windows® refers to the Microsoft® Windows® operating system.

Windows® 98 is Microsoft® Windows® 98 operating system.

Windows® Me is Microsoft® Windows® Me operating system.

Windows NT® is Microsoft® Windows NT® operating system.

Windows® XP refers to the Microsoft® Windows® XP operating system.

Windows Vista® is Microsoft® Windows Vista® operating system

Windows Server® 2003 refers to the Microsoft® Windows Server® 2003 operating system.

Windows Server® 2008 refers to the Microsoft® Windows Server® 2008 operating system.

Windows Server® 2012 refers to the Microsoft® Windows Server® 2012 operating system.

Microsoft, Windows, Windows NT and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.